



P1000 JAT Infrared brooder for 1000 broilers CPIJ0204005

The brooders are designed with a detachable system that is unique in the market, no tools or specialized technicians are required for its maintenance and cleaning. 15 seconds are enough to clean disassemble and reassemble, ensuring correct operation and optimization of gas in order to obtain a better combustion gas and saving.

Capacity

Approximately 1000 broiler chicks per brooder.

Advantages

- ◆ Compact design, fits where required.
- ◆ Lightweight, easy to handle and move.
- ◆ Easy maintenance, specialized tools are not required.
- ◆ Composed with premium raw materials.
- ◆ High intensity infrared rays that directly heats the chickens in the bed.

Materials

- ◆ Made of stainless steel, aluminum, and brass for a longer useful lifetime.

- 1 Adjustable chain link
- 2 Stainless steel tensor
- 3 Security device
- 4 Air-gas mixer
- 5 Rotating air filter
- 6 Tube with safety clip
- 7 Aluminum bell for a efficient refraction
- 8 High resistant mesh diffuser



PERFORMANCE	Kcla/hr.	BTU/hrs.
Minimum:	475	1885
Maximum:	3599	14280
Gas:	60% Butane and 40% Propane	
Operating pressure:	0.5 a 6 lb	
Maximum consumption:	303 gr/hrs	
Dimensions:	69,5 x 16 x 48 cm	
Weight:	2.150 kg	

CONSUMPTION			
Pressure	Consumtion	Performance	
(lb)	gr/hrs	kcal/hrs	BTU/hrs
0.5	40	475	1885
1	82.5	980	3888
2	165	1960	7776
3	210	2494	9897
4	252	2993	11876
5	275	3266	12960
6	303	3599	14280

