



Automatic Incubators.

Characteristics

- ◆ Automatic turning system of 45° every 2 hours.
- ◆ Door with panoramic view with double glass and integrated thermometer.
- ◆ Internal light to improve visibility.
- ◆ It has a water tank to keep humidity inside the incubator.
- ◆ Controlled tray by floater with deposit of 25 liters.

Advantages

- ◆ Wheels for easy handling.
- ◆ 3-step shifter (automatic, manual and off).
- ◆ Aluminum angle on the outside for better protection.
- ◆ Interior ventilation based on motor.

Electric system

- ◆ 15 amperes loading center. for protection against electrical discharges.
- ◆ Equipped with digital temperature control or micro and wafer system.
- ◆ Single-phase power consumption of 300 or 450 watts.

Material

Fabricate of melamine.
Fabricate of liner panel (fiberglass) double panel.

Different Species

Our incubators can be used for different birds, varying only the incubation time according to each species, among which are: Chicken, Quail, Turkey, Duck, Peacock, Pheasant, Goose, Coquena.



Capacity

Model	Capacity	Incubation tray	Hatching capacity	Hatching tray	Temperature control system		Turning System		Measure	Weight
					Digital	Micro & Wafer	Manual	Automatic		
INCU0303002	48 eggs	1	-	-	✓	✓		✓	85 x 46 x 77	25.0 Kgs.
INCU0204003	90 eggs	1	90 eggs	1	✓	✓		✓	110 x 46 x 77	31.0 Kgs.
INCU0204004	180 eggs	2	180 eggs	2	✓	✓		✓	110 x 46 x 77	31.0 Kgs.
INCU0204006	270 eggs	3	100 eggs	1	✓	✓		✓	110 x 46 x 77	31.0 Kgs.
INCU0204016	500 eggs	3	500 eggs	3	✓	✓		✓	150x126x56	77.0 Kgs.
INCU0204014	720 eggs	4	240 eggs	2	✓	✓		✓	150x126x56	77.0 Kgs.
INCU0204012	1,020 eggs	7	-	-	✓	✓		✓	150x126x56	77.0 Kgs.
INCU0204010	1,200 eggs	10	-	10	✓	✓	✓		150x126x56	77.0 Kgs.
INCU0204030	2,000 eggs	14	-	-	✓	✓		✓	175x125x76	130.0 Kgs.